

212

Ceramic end window

GENERAL SPECIFICATIONS

GAS PRESSURE (TORR)	760
CATHODE MATERIAL (INTERNAL/EXTERNAL)	Stainless Steel
MAXIMUM LENGTH (INCH/MM)	16.0/406.40
EFFECTIVE LENGTH (INCH/MM)	12.75/323.85
MAXIMUM DIAMETER (INCH/MM)	2.0/50.8
EFFECTIVE DIAMETER (INCH/MM)	1.87/47.5
CONNECTOR	RT Angle HN
EFFECTIVE VOLUME (CM³)	573.54
OPERATING TEMPERATURE RANGE °C	-50 to +100

WINDOW SPECIFICATIONS

MATERIAL	Al203
THICKNESS (INCH/MM)	1.93 / 49.0

ELECTRICAL SPECIFICATIONS

RECOMMENDED OPERATING VOLTAGE (VOLTS)	2200
OPERATING VOLTAGE RANGE (VOLTS)	2100 - 2300
MAXIMUM PLATEAU SLOPE (%/100 VOLTS)	1
MAXIMUM RESOLUTION (% FWHM)	40
TUBE CAPACITANCE (PF)	8
WEIGHT (GRAMS)	500

THERMAL NEUTRON SENSITIVITY

SENSITIVITY (CPS/NV)	25.1
----------------------	------

