

221

Quadrilateral bf3 detector

## GENERAL SPECIFICATIONS

<b>MAXIMUM LENGTH (INCH/MM)</b>	11.23/285.24
<b>EFFECTIVE LENGTH (INCH/MM)</b>	8.0/203.2
<b>CATHODE MATERIAL (INTERNAL/EXTERNAL)</b>	Stainless Steel
<b>CONNECTOR</b>	HN
<b>OPERATING TEMPERATURE RANGE °C</b>	-50 to +100
<b>MAXIMUM WIDTH (INCH/MM)</b>	1.0/25.4
<b>GAS PRESSURE (TORR)</b>	400
<b>EFFECTIVE VOLUME (CM<sup>3</sup>)</b>	83.36
<b>EFFECTIVE WIDTH (INCH/MM)</b>	0.9/22.86

## ELECTRICAL SPECIFICATIONS

<b>RECOMMENDED OPERATING VOLTAGE (VOLTS)</b>	1200
<b>OPERATING VOLTAGE RANGE (VOLTS)</b>	1100 - 1350

MAXIMUM PLATEAU SLOPE (%/100 VOLTS)	1
TUBE CAPACITANCE (PF)	7
WEIGHT (GRAMS)	340
MAXIMUM RESOLUTION (% FWHM)	8

## THERMAL NEUTRON SENSITIVITY

SENSITIVITY (CPS/NV)	1.9
----------------------	-----

