

23211

Boron lined neutron proportional counter

GENERAL SPECIFICATIONS

MAXIMUM LENGTH (INCH/MM)	29.6/751.8
MAXIMUM DIAMETER (INCH/MM)	1.0/25.4
GAS FILLING	Argon
EFFECTIVE LENGTH (INCH/MM)	26.0/660.4
CATHODE MATERIAL (INTERNAL/EXTERNAL)	Stainless Steel
EFFECTIVE DIAMETER (INCH/MM)	0.93/23.6
CONNECTOR	HN
OPERATING TEMPERATURE RANGE °C	-50 to +100
GAS PRESSURE (TORR)	200
EFFECTIVE VOLUME (CM ³)	289.3

OPERATING CHARACTERISTICS

RECOMMENDED OPERATING VOLTAGE (VOLTS)	800
---------------------------------------	-----

OPERATING VOLTAGE RANGE (VOLTS)	700 - 950
MAXIMUM PLATEAU SLOPE (%/100 VOLTS)	30
TUBE CAPACITANCE (PF)	4
THERMAL NEUTRON SENSITIVITY (CPS/NV)	10.0
FLUX RANGE	1.0E-1 - 1.0E4

NEUTRON SENSITIVE MATERIAL

COATING MATERIAL	B10
ENRICHMENT (%)	96
COATED THICKNESS (MG/CM²)	0.5
COATED AREA (CM²)	180.0

