

# 2511

Cylindrical he3 neutron detector

## GENERAL SPECIFICATIONS

<b>MAXIMUM LENGTH (INCH/MM)</b>	8.44/214.38
<b>MAXIMUM DIAMETER (INCH/MM)</b>	0.5/12.7
<b>EFFECTIVE LENGTH (INCH/MM)</b>	6/152.4
<b>CATHODE MATERIAL (INTERNAL/EXTERNAL)</b>	Stainless Steel
<b>EFFECTIVE DIAMETER (INCH/MM)</b>	0.4/10.16
<b>CONNECTOR</b>	Flying Lead
<b>OPERATING TEMPERATURE RANGE °C</b>	-50 to +100
<b>GAS PRESSURE (TORR)</b>	8360
<b>EFFECTIVE VOLUME (CM<sup>3</sup>)</b>	12.35

## ELECTRICAL SPECIFICATIONS

<b>RECOMMENDED OPERATING VOLTAGE (VOLTS)</b>	3000
<b>OPERATING VOLTAGE RANGE (VOLTS)</b>	2800 - 3200

MAXIMUM PLATEAU SLOPE (%/100 VOLTS)	1
TUBE CAPACITANCE (PF)	7
WEIGHT (GRAMS)	255
MAXIMUM RESOLUTION (% FWHM)	7

## THERMAL NEUTRON SENSITIVITY

SENSITIVITY (CPS/NV)	7.6
----------------------	-----

