

# 426

Quadrilateral side window proportional counter

## GENERAL SPECIFICATIONS

<b>MAXIMUM LENGTH (INCH/MM)</b>	8.31/211.07
<b>GAS FILLING</b>	Argon
<b>EFFECTIVE LENGTH (INCH/MM)</b>	5.45/138.43
<b>CATHODE MATERIAL (INTERNAL/EXTERNAL)</b>	Aluminum
<b>CONNECTOR</b>	MHV
<b>OPERATING TEMPERATURE RANGE °C</b>	-40 to +75
<b>MAXIMUM WIDTH (INCH/MM)</b>	3.0/76.2
<b>GAS PRESSURE (TORR)</b>	800
<b>EFFECTIVE WIDTH (INCH/MM)</b>	2.75/69.85
<b>PATH LENGTH (INCH/MM)</b>	2.75/69.85

## WINDOW SPECIFICATIONS

<b>MATERIAL</b>	Beryllium
-----------------	-----------

THICKNESS (INCH/MM)	0.002/0.05
AREAL DENSITY (MG/CM <sup>2</sup> )	9.2
DIMENSIONS (INCH/MM)	1.75 x 1.75/44.45 x 44.45

## ELECTRICAL SPECIFICATIONS

RECOMMENDED OPERATING VOLTAGE (VOLTS)	1850
OPERATING VOLTAGE RANGE (VOLTS)	1750 - 2000
CAPACITANCE (PF)	3
TYPICAL RESOLUTION (FWHM FE55)	18



