

# 45321

Beryllium side window proportional counter

## GENERAL SPECIFICATIONS

<b>MAXIMUM LENGTH (INCH/MM)</b>	3.55/90.17
<b>MAXIMUM DIAMETER (INCH/MM)</b>	1.5/38.1
<b>GAS FILLING</b>	Neon
<b>EFFECTIVE LENGTH (INCH/MM)</b>	2.0/50.8
<b>CATHODE MATERIAL (INTERNAL/EXTERNAL)</b>	Aluminum
<b>EFFECTIVE DIAMETER (INCH/MM)</b>	1.43/36.32
<b>CONNECTOR</b>	Pin
<b>OPERATING TEMPERATURE RANGE °C</b>	-40 to +75
<b>GAS PRESSURE (TORR)</b>	800
<b>PATH LENGTH (INCH/MM)</b>	1.43/36.32

## WINDOW SPECIFICATIONS

<b>MATERIAL</b>	Beryllium
-----------------	-----------

THICKNESS (INCH/MM)	0.005/0.13
AREAL DENSITY (MG/CM <sup>2</sup> )	23
DIAMETER (INCH/MM)	0.75/19.05

## ELECTRICAL SPECIFICATIONS

RECOMMENDED OPERATING VOLTAGE (VOLTS)	1000
OPERATING VOLTAGE RANGE (VOLTS)	900-1150
CAPACITANCE (PF)	3
TYPICAL RESOLUTION (FWHM FE55)	20

