

# 45621

Dual window flow proportional counter

## GENERAL SPECIFICATIONS

<b>MAXIMUM LENGTH (INCH/MM)</b>	4.48/113.8
<b>MAXIMUM DIAMETER (INCH/MM)</b>	1.88/47.8
<b>GAS FILLING</b>	P10
<b>EFFECTIVE LENGTH (INCH/MM)</b>	2.18/55.4
<b>CATHODE MATERIAL (INTERNAL/EXTERNAL)</b>	Aluminum
<b>EFFECTIVE DIAMETER (INCH/MM)</b>	0.88/22.4
<b>CONNECTOR</b>	Pin
<b>OPERATING TEMPERATURE RANGE °C</b>	0 to +50

## OPERATING CHARACTERISTICS

<b>RECOMMENDED OPERATING VOLTAGE (VOLTS)</b>	1500
<b>OPERATING VOLTAGE RANGE (VOLTS)</b>	1400 - 1650
<b>CAPACITANCE (PF)</b>	3

TYPICAL RESOLUTION (FWHM FE55)	16
--------------------------------	----

## EXIT WINDOW SPECIFICATIONS

MATERIAL	Mylar
AREAL DENSITY (MG/CM <sup>2</sup> )	0.8
DIMENSIONS (INCH/MM)	0.56 x 0.88/14.2 x 22.3

## ENTRANCE WINDOW SPECIFICATIONS

MATERIAL	Mylar
AREAL DENSITY (MG/CM <sup>2</sup> )	0.8
DIMENSIONS (INCH/MM)	0.56 x 0.88/14.2 x 22.3

