

# 45669

Beryllium side window proportional counter

## GENERAL SPECIFICATIONS

<b>MAXIMUM LENGTH (INCH/MM)</b>	4.56/115.8
<b>MAXIMUM DIAMETER (INCH/MM)</b>	1.0/25.4
<b>GAS FILLING</b>	Xenon
<b>EFFECTIVE LENGTH (INCH/MM)</b>	2.66/67.5
<b>CATHODE MATERIAL (INTERNAL/EXTERNAL)</b>	Stainless Steel
<b>EFFECTIVE DIAMETER (INCH/MM)</b>	0.78/19.8
<b>CONNECTOR</b>	Pin
<b>OPERATING TEMPERATURE RANGE °C</b>	-40 to +75
<b>GAS PRESSURE (TORR)</b>	800
<b>PATH LENGTH (INCH/MM)</b>	0.78/19.8

## WINDOW SPECIFICATIONS

<b>MATERIAL</b>	Beryllium
-----------------	-----------

THICKNESS (INCH/MM)	0.002/0.05
AREAL DENSITY (MG/CM <sup>2</sup> )	9.2
DIMENSIONS (INCH/MM)	0.38 x 1.0/9.5 x 25.4

## ELECTRICAL SPECIFICATIONS

RECOMMENDED OPERATING VOLTAGE (VOLTS)	1900
OPERATING VOLTAGE RANGE (VOLTS)	1800 - 2050
CAPACITANCE (PF)	3
TYPICAL RESOLUTION (FWHM FE55)	18



