

# 49733

Large area – beta – gamma proportional counter

## GENERAL SPECIFICATIONS

<b>MAXIMUM LENGTH (INCH/MM)</b>	9.64/244.9
<b>GAS FILLING</b>	Xenon
<b>EFFECTIVE LENGTH (INCH/MM)</b>	6.45/163.8
<b>CATHODE MATERIAL (INTERNAL/EXTERNAL)</b>	Aluminum
<b>CONNECTOR</b>	MHV
<b>OPERATING TEMPERATURE RANGE °C</b>	0 to +50
<b>MAXIMUM WIDTH (INCH/MM)</b>	4.69/119.1
<b>GAS PRESSURE (TORR)</b>	800
<b>EFFECTIVE WIDTH (INCH/MM)</b>	4.08/103.7
<b>PATH LENGTH (INCH/MM)</b>	0.50/12.7

## WINDOW SPECIFICATIONS

<b>MATERIAL</b>	Titanium
-----------------	----------

THICKNESS (INCH/MM)	0.00047/0.012
AREAL DENSITY (MG/CM <sup>2</sup> )	5.0
EFFECTIVE AREA (CM <sup>2</sup> )	140

## ELECTRICAL SPECIFICATIONS

RECOMMENDED OPERATING VOLTAGE (VOLTS)	1450
OPERATING VOLTAGE RANGE (VOLTS)	1350 - 1600
GAMMA SENSITIVITY CO60 (CPS/mR/HR)	600
MINIMUM COUNTING LIFE (COUNTS)	1.0E12
PLATEAU SLOPE (%/100 VOLTS)	2

