

50422

High pressure gamma ionization chamber

GENERAL SPECIFICATIONS

MAXIMUM LENGTH (INCH/MM)	7.72/196.1
MAXIMUM DIAMETER (INCH/MM)	3.5/88.9
EFFECTIVE LENGTH (INCH/MM)	4.5/114.3
CATHODE MATERIAL (INTERNAL/EXTERNAL)	Stainless Steel
FILL GAS	Argon
FILL PRESSURE (TORR)	31920
EFFECTIVE VOLUME (CM ³)	400.0
OUTER CASING MATERIAL	Stainless Steel
ANODE CONNECTOR	MHV
CATHODE CONNECTOR	MHV
GUARD CONNECTOR	N/A

OPERATING CHARACTERISTICS

RECOMMENDED OPERATING VOLTAGE (VOLTS)	500
OPERATING TEMPERATURE RANGE °C	-50 to +100
MAXIMUM OPERATING VOLTAGE (VOLTS)	2000
GAMMA SENSITIVITY (A/R/HR - CO60)	2.1E-9
RESISTANCE - SIGNAL ELECTRODE TO CATHODE (OHMS)	>1.0E12
RESISTANCE - GUARD ELECTRODE TO CATHODE (OHMS)	>1.0E9

