

72314

End window-alpha-beta-gamma detector

GENERAL SPECIFICATIONS

MAXIMUM LENGTH (INCH/MM)	1.93/49.1
MAXIMUM DIAMETER (INCH/MM)	1.31/33.3
GAS FILLING	Ne +Halogen
EFFECTIVE LENGTH (INCH/MM)	1.45/36.8
CATHODE MATERIAL (INTERNAL/EXTERNAL)	446 Stainless Steel
EFFECTIVE DIAMETER (INCH/MM)	1.13/28.6
CONNECTOR	Pin
OPERATING TEMPERATURE RANGE °C	-40 to +75

WINDOW SPECIFICATIONS

MATERIAL	Mica
EFFECTIVE DIAMETER (INCH/MM)	1.13/28.6
AREAL DENSITY (MG/CM²)	2.0

ELECTRICAL SPECIFICATIONS

RECOMMENDED OPERATING VOLTAGE (VOLTS)	500
RECOMMENDED ANODE RESISTOR (MEG OHM)	4.7
OPERATING VOLTAGE RANGE (VOLTS)	450 - 700
MAXIMUM PLATEAU SLOPE (%/100 VOLTS)	10
MINIMUM DEAD TIME (MICRO SEC)	230
GAMMA SENSITIVITY CO60 (CPS/mR/HR)	50
TUBE CAPACITANCE (PF)	3
WEIGHT (GRAMS)	51
MAXIMUM BACKGROUND SHIELDED 50MM PB + 3MM AL (CPM)	25
MAXIMUM STARTING VOLTAGE (VOLTS)	375
MINIMUM ANODE RESISTOR (MEG OHM)	3.3







