

7232

End window-alpha-beta-gamma detector



GENERAL SPECIFICATIONS

MAXIMUM LENGTH (INCH/MM)	4.85/123.1
MAXIMUM DIAMETER (INCH/MM)	1.38/34.9
GAS FILLING	Ne +Halogen
EFFECTIVE LENGTH (INCH/MM)	2.6/66.04
CATHODE MATERIAL (INTERNAL/EXTERNAL)	446 Stainless Steel
EFFECTIVE DIAMETER (INCH/MM)	1.13/28.6
CONNECTOR	BNC
OPERATING TEMPERATURE RANGE °C	-55 to +75

WINDOW SPECIFICATIONS

MATERIAL	Mica
EFFECTIVE DIAMETER (INCH/MM)	1.13/28.6
AREAL DENSITY (MG/CM²)	2.0

ELECTRICAL SPECIFICATIONS

RECOMMENDED OPERATING VOLTAGE (VOLTS)	900
RECOMMENDED ANODE RESISTOR (MEG OHM)	1
OPERATING VOLTAGE RANGE (VOLTS)	850-1000
MAXIMUM PLATEAU SLOPE (%/100 VOLTS)	10
MINIMUM DEAD TIME (MICRO SEC)	150
GAMMA SENSITIVITY CO60 (CPS/mR/HR)	40
TUBE CAPACITANCE (PF)	3
WEIGHT (GRAMS)	155
MAXIMUM BACKGROUND SHIELDED 50MM PB + 3MM AL (CPM)	50
MAXIMUM STARTING VOLTAGE (VOLTS)	800







