

# 7237

End window alpha-beta-gamma detector

## GENERAL SPECIFICATIONS

<b>MAXIMUM LENGTH (INCH/MM)</b>	4.85/123.1
<b>MAXIMUM DIAMETER (INCH/MM)</b>	1.38/34.9
<b>GAS FILLING</b>	Ne +Halogen
<b>EFFECTIVE LENGTH (INCH/MM)</b>	2.6/66.0
<b>CATHODE MATERIAL (INTERNAL/EXTERNAL)</b>	446 Stainless Steel
<b>EFFECTIVE DIAMETER (INCH/MM)</b>	1.13/28.6
<b>CONNECTOR</b>	MHV
<b>OPERATING TEMPERATURE RANGE °C</b>	-55 to +75

## WINDOW SPECIFICATIONS

<b>MATERIAL</b>	Mica
<b>EFFECTIVE DIAMETER (INCH/MM)</b>	1.13/28.6
<b>AREAL DENSITY (MG/CM<sup>2</sup>)</b>	2.0

# ELECTRICAL SPECIFICATIONS

RECOMMENDED OPERATING VOLTAGE (VOLTS)	900
RECOMMENDED ANODE RESISTOR (MEG OHM)	1
OPERATING VOLTAGE RANGE (VOLTS)	850-1000
MAXIMUM PLATEAU SLOPE (%/100 VOLTS)	10
MINIMUM DEAD TIME (MICRO SEC)	150
GAMMA SENSITIVITY CO60 (CPS/mR/HR)	45
TUBE CAPACITANCE (PF)	3
WEIGHT (GRAMS)	155
MAXIMUM BACKGROUND SHIELDED 50MM PB + 3MM AL (CPM)	50
MAXIMUM STARTING VOLTAGE (VOLTS)	800



