

72422

End window-alpha-beta-gamma detector

GENERAL SPECIFICATIONS

MAXIMUM LENGTH (INCH/MM)	1.03/26.1
MAXIMUM DIAMETER (INCH/MM)	1.0/25.4
GAS FILLING	Ne +Halogen
EFFECTIVE LENGTH (INCH/MM)	0.35/8.89
CATHODE MATERIAL (INTERNAL/EXTERNAL)	446 Stainless Steel
EFFECTIVE DIAMETER (INCH/MM)	0.78/19.8
CONNECTOR	Solder Clip
OPERATING TEMPERATURE RANGE °C	-40 to +75

WINDOW SPECIFICATIONS

MATERIAL	Mica
EFFECTIVE DIAMETER (INCH/MM)	0.78/19.8
AREAL DENSITY (MG/CM²)	2.0 - 3.0

ELECTRICAL SPECIFICATIONS

RECOMMENDED OPERATING VOLTAGE (VOLTS)	900
RECOMMENDED ANODE RESISTOR (MEG OHM)	4.7
OPERATING VOLTAGE RANGE (VOLTS)	850-1050
MAXIMUM PLATEAU SLOPE (%/100 VOLTS)	10
MINIMUM DEAD TIME (MICRO SEC)	50
GAMMA SENSITIVITY CO60 (CPS/mR/HR)	12
TUBE CAPACITANCE (PF)	3
WEIGHT (GRAMS)	18
MAXIMUM BACKGROUND SHIELDED 50MM PB + 3MM AL (CPM)	8
MAXIMUM STARTING VOLTAGE (VOLTS)	790
MINIMUM ANODE RESISTOR (MEG OHM)	3.3





