

7243

End window-alpha-beta-gamma detector

GENERAL SPECIFICATIONS

MAXIMUM LENGTH (INCH/MM)	0.75/19.1
MAXIMUM DIAMETER (INCH/MM)	0.71/18.0
GAS FILLING	Ne +Halogen
EFFECTIVE LENGTH (INCH/MM)	0.25/6.35
CATHODE MATERIAL (INTERNAL/EXTERNAL)	446 Stainless Steel
EFFECTIVE DIAMETER (INCH/MM)	0.63/15.9
CONNECTOR	Pin
OPERATING TEMPERATURE RANGE °C	-40 to +75

WINDOW SPECIFICATIONS

MATERIAL	Mica
EFFECTIVE DIAMETER (INCH/MM)	0.63/15.9
AREAL DENSITY (MG/CM²)	2.0

ELECTRICAL SPECIFICATIONS

RECOMMENDED OPERATING VOLTAGE (VOLTS)	500
RECOMMENDED ANODE RESISTOR (MEG OHM)	3.3
OPERATING VOLTAGE RANGE (VOLTS)	450 - 650
MAXIMUM PLATEAU SLOPE (%/100 VOLTS)	8
MINIMUM DEAD TIME (MICRO SEC)	45
GAMMA SENSITIVITY CO60 (CPS/mR/HR)	6
TUBE CAPACITANCE (PF)	3
WEIGHT (GRAMS)	10
MAXIMUM BACKGROUND SHIELDED 50MM PB + 3MM AL (CPM)	4
MAXIMUM STARTING VOLTAGE (VOLTS)	350
MINIMUM ANODE RESISTOR (MEG OHM)	2.7





