

743

Gamma detector



GENERAL SPECIFICATIONS

MAXIMUM LENGTH (INCH/MM)	7.61/193.2
MAXIMUM DIAMETER (INCH/MM)	0.63/16.0
GAS FILLING	Ne +Halogen
EFFECTIVE LENGTH (INCH/MM)	5.81/147.6
CATHODE MATERIAL (INTERNAL/EXTERNAL)	446 Stainless Steel
EFFECTIVE DIAMETER (INCH/MM)	0.61/15.5
CONNECTOR	Jedec A3-1
OPERATING TEMPERATURE RANGE °C	-55 to +75

ELECTRICAL SPECIFICATIONS

RECOMMENDED OPERATING VOLTAGE (VOLTS)	900
RECOMMENDED ANODE RESISTOR (MEG OHM)	1
OPERATING VOLTAGE RANGE (VOLTS)	850-1000
MAXIMUM PLATEAU SLOPE (%/100 VOLTS)	15
MINIMUM DEAD TIME (MICRO SEC)	75
GAMMA SENSITIVITY CO60 (CPS/mR/HR)	60
TUBE CAPACITANCE (PF)	3
WEIGHT (GRAMS)	24
MAXIMUM BACKGROUND SHIELDED 50MM PB + 3MM AL (CPM)	50
MAXIMUM STARTING VOLTAGE (VOLTS)	800





