

4534

Beryllium side window proportional counter

GENERAL SPECIFICATIONS

MAXIMUM LENGTH (INCH/MM)	3.55/90.1
MAXIMUM DIAMETER (INCH/MM)	1.5/38.1
GAS FILLING	Xenon
EFFECTIVE LENGTH (INCH/MM)	2.00/50.8
CATHODE MATERIAL (INTERNAL/EXTERNAL)	Aluminum
EFFECTIVE DIAMETER (INCH/MM)	1.25/31.75
CONNECTOR	Pin
OPERATING TEMPERATURE RANGE °C	-40 to +75
GAS PRESSURE (TORR)	800
PATH LENGTH (INCH/MM)	1.25/31.75

WINDOW SPECIFICATIONS

MATERIAL	Beryllium
-----------------	-----------

THICKNESS (INCH/MM)	0.002/0.05
AREAL DENSITY (MG/CM ²)	9.2
DIAMETER (INCH/MM)	1.0/25.4

ELECTRICAL SPECIFICATIONS

RECOMMENDED OPERATING VOLTAGE (VOLTS)	1600
OPERATING VOLTAGE RANGE (VOLTS)	1500 - 1750
CAPACITANCE (PF)	3
TYPICAL RESOLUTION (FWHM FE55)	18

